



PAFI

Iron / Sulphur Filters



Shown With 2400 Valve
And
Optional Bypass Valve

Enjoy:

- ◆ No More Rusty Red Iron Stains
- ◆ No More Rotten Egg (Sulphide) Odour
- ◆ Savings on Soap And Cleaning Products.
- ◆ Reduced Maintenance On Household Appliances and Fixtures.
- ◆ Savings On Time And Money

Features:

- ◆ Fully Automatic Operation
- ◆ High Reliability
- ◆ Safe Low Voltage Operation
- ◆ High Efficiency
- ◆ Large Ported Valve Maximizes Water Delivery
- ◆ Includes Carbon Bed for Chlorine Taste and Odour Removal
- ◆ Permanent Storage of Settings Means No Batteries



with





568 ROTARY CONTROL



AIR INJECTOR

PAFI Iron / Sulphur Filters



- Simple user interface puts you informed and in control over all functions.
- Immediately begins to monitor water usage and automatically adjusts to your changing water needs.
- Oversize porting allows copious water delivery to meet the growing demand of the modern lifestyle.
- Superior reliability achieved by only three moving parts.
- Backed by over 50 years of valve engineering and manufacturing experience
- Let us show you how simple and reliable conditioned water can be.

Unit Specifications

Model	Capacity	Conditioner	Flow Rate
	Grains	Depth X Width X Height Inch (cm)	Backwash USGPM (l/min.)
PAFI24844	7.9K	8 X 8 X 54 (20 X 20 X 131)	3.5 (14)
PAFI24948	11.2K	9 X 9 X 58 (23 X 23 X 140)	4.0 (16)
PAFI241047	12.5K	10 X 10 X 57 (25 X 25 X 138)	5.0 (19)
PAFI241252	19.6K	12 X 12 X 62 (30 X 30 X 152)	8.0 (31)
PAFI-844	7.9K	8 X 8 X 54 (20 X 20 X 131)	3.5 (14)
PAFI-948	11.2K	9 X 9 X 58 (23 X 23 X 140)	4.0 (16)
PAFI-1047	12.5K	10 X 10 X 57 (25 X 25 X 138)	5.0 (19)
PAFI-1252	19.6K	12 X 12 X 62 (30 X 30 X 152)	8.0 (31)
VT-1047	Optional	10 X 10 X 50 cr (25 X 25 X 121)	

General Unit Requirements

	Maximum		Minimum	
	Metric	Imperial	Metric	Imperial
Operating Temperature	50° C	120° F.	2° C	35° F.
Operating Pressure	8.28 bar	120 psi	1.37 bar	25 psi
Supply Voltage	120 VAC			
Operating Voltage	24 VAC			
Power Requirement	6 Watts Continuous 10 Watts Intermittent			

Manufacturer:



WATER QUALITY
CONTROL SYSTEMS LIMITED

605 Denison Street, Markham, Ontario, Canada, L3R 1B8
Tel: 905-944-9465 1-888-830-5776 Fax: 905-944-0504
www.purifiner.com sales@wqcs.com

Dealer:

