



Purifiner®

PDS-MB Hardness / Chlorine / Taste & Odour Systems



Features:

- ◆ Fully Automatic Operation
- ◆ High Reliability
- ◆ Safe Low Voltage Operation
- ◆ High Efficiency
- ◆ Large Ported Valve Maximizes Water Delivery
- ◆ Includes Carbon Bed for Chlorine Taste and Odour Removal
- ◆ Permanent Storage of Settings Means No Batteries

Enjoy:

- ◆ Water That Feels, Tastes And Smells Better.
- ◆ Savings on Soap And Cleaning Products.
- ◆ Reduced Maintenance On Household Appliances and Fixtures.
- ◆ Savings On Time And Money



with



PDS-MB *Hardness / Iron / Chlorine / Taste & Odour Systems*



BATHING:

Calcium and magnesium carbonate in water combine with soap and shampoo to form a soap film on the skin and scalp. This film can retain dirt and bacteria and can cause drying of the skin. Softening your water removes this film from your body and reduces the deposition on water fixtures.



LAUNDRY:

Cleaning agents in detergents, grease and oils in dirty laundry water combine to form soap curds in hard water. Conditioned water prevents these formations, leaving clothes brighter and softer and lasting longer. You will also save money through the use of mild soap in your laundry instead of costly harsh detergents.



ODOUR CONTROL:

Eliminates odours associated with chlorination and its by-products. Making your water much more pleasing in the shower, at the sink and in your home environment in general.

STAINING:

Water bearing iron can cause red to brown staining on water fixtures and have a metallic taste. Removal of this iron reduces the unsightly mess and extends the life of these expensive items. It also improves the taste of water for cooking and as a beverage.



PLUMBING:

Hard water can cause unseen problems with scale formation in plumbing fixtures, pipes and water heaters. Heavy scale can reduce water flow and significantly reduce the efficiency of your water heater. Conditioned water reduces this buildup and greatly increases efficiency while reducing maintenance costs.



DISH WASHING:

Hard water combines with soaps and detergents in dishwashers and leaves deposits as spots on your dishes, glassware and utensils. Conditioned water reduces spotting and allows savings in lower detergent usage.



- Simple user interface puts you informed and in control over all functions.
- Immediately begins to monitor water usage and automatically adjusts to your changing water needs.
- Oversize porting allows copious water delivery to meet the growing demand of the modern lifestyle.
- Superior reliability achieved by only three moving parts.
- Backed by over 50 years of valve engineering and manufacturing experience
- Let us show you how simple and reliable conditioned water can be.

Unit Specifications

	Model	Capacity Grains	Conditioner	Brine Tank
			Depth X Width X Height	Diameter X Height
			Inch (cm)	Inch (cm)
White Jacket	PDS-20MB	20K	14 X 8 X 53 (35 X 20 X 130)	16 X 35 (40 X 86)
	PDS-30MB	30K	14 X 10 X 56 (35 X 25 X 138)	16 X 35 (40 X 86)
	PDS-40MB	40K	14 X 10 X 63 (35 X 25 X 155)	16 X 35 (40 X 86)
	PDS-45MB	45K	14 X 12 X 61 (35 X 30 X 150)	18 X 33 (45 X 81)
	PDS-60MB	60K	14 X 13 X 63 (35 X 32 X 155)	18 X 40 (45 X 98)
Chrome Jacket	PDS-20MBC	20K	14 X 8 X 53 (35 X 20 X 130)	16 X 35 (40 X 86)
	PDS-30MBC	30K	14 X 10 X 56 (35 X 25 X 138)	16 X 35 (40 X 86)
	PDS-40MBC	40K	14 X 10 X 63 (35 X 25 X 155)	16 X 35 (40 X 86)
	PDS-45MBC	45K	14 X 12 X 61 (35 X 30 X 150)	18 X 33 (45 X 81)
	PDS-60MBC	60K	14 X 13 X 63 (35 X 32 X 155)	18 X 40 (45 X 98)

General Unit Requirements

	Maximum		Minimum	
	Metric	Imperial	Metric	Imperial
Operating Temperature	50° C	120° F.	2° C	35° F.
Operating Pressure	8.28 bar	120 psi	1.37 bar	25 psi
Supply Voltage	120 VAC			
Operating Voltage	24 VAC			
Power Requirement	6 Watts Continuous 10 Watts Intermittent			



Manufacturer:



WATER QUALITY
CONTROL SYSTEMS LIMITED

605 Denison Street, Markham, Ontario, Canada, L3R 1B8
Tel: 905-944-9465 1-888-830-5776 Fax: 905-944-0504
www.purifiner.com sales@wqcs.com

Dealer:

