



## SW20M – Specification

Product Description: Air Cooled High Frequency Corona Discharge Ozone Generator

Typical Applications: Potable water, wastewater, pools, service water, aquaculture

Configurations:	Wall configuration with front mounted controls	<u>Order Code</u>
	Rack configuration with end mounted controls	FRAME-SS
	Water Cooled Option	SW10M/W

Features:

- High Pressure tolerance on feed gas to 40 psi.
- High Performance & long life ceramic dielectric
- Low energy consumption
- 2 year warranty on all components

	SW20M
<b>Gr/hr @ 2 l/min PSA Oxygen</b>	22.0
<b>Gr/hr @ 8 l/min Dry Air</b>	10.4
<b>Energy</b>	200 w
<b>Amp draw @120v/60hz</b>	2.8
<b>Power @ 60/50 hz</b>	120-240v
<b>Manual Variable Control</b>	Optional
<b>Automatic 4-20ma Control</b>	Optional
<b>High Temp Limit</b>	Yes
<b>Air Flow Meter</b>	Optional
<b>Water Cooling</b>	Optional
<b>Cooling Water Shutoff</b>	Automatic
<b>Air Cooling</b>	Yes
<b>Size (h x w x d)</b>	61 x 43 x 18 cm
<b>Weight</b>	4.5 kg

